
## Special tool

Tester for vacuum systems




116 589 25 21 00

## a) Testing vacuum switch


1 Pull vacuum line from vacuum switch (19, 20, 23 and 81) and connect tester.

- 2 Connect ohmmeter to vacuum switch (19, 20, 23 and 81).
- 3 Evacuate vacuum switch. Vacuum switch (19) closes at 175 mbar vacuum (0.18 atu), the vacuum switches (20, 23 and 81) at 78.5 mbar vacuum (0.08 atu). Ohmmeter indicates passage.
- 6 Amplifier 9 Blower 18 Double contact relay
- 9 Vacuum switch (main switch, green)
- 20 Vacuum switch(refrigerant compressor, yellow)
- 21 Temperature switch for heating water pump
- 45 Air jet nozzle



## b) Testing switchover valves (28 and 29) for operation and leaks

- 4 Remove vacuum lines and electric plug from switchover valve (28 and 29).
- 5 Connect tester to upper connection of switchover valve (28 and 29) and evacuate.
  - 23 Vacuum switch for refrigerant compressor (at "BI-LEVEL" only)
  - 28 Switchover valve
  - 29 Switchover valve
  - 30 Vacuum lines
  - 34 Check valve
- 38 Specified leak point 80 Switchover valve ("BI-LEVEL")
- 81 Vacuum switch (at "BI-LEVEL" only)
  - 2 Check valve
- 83 Check valve




- 6 If gauge shows a pressure increase, switchover valve is leaking.
- 7 Energize switchover valve. Switchover valve opens, readout on gauge drops.

- c) Testing switchover valve (80) for operation and leaks
- 8 Remove vacuum line (black) and electric plug from switchover valve (80).
  - 23 Vacuum switch for refrigerant compressor (at "BI-LEVEL" only)
    28 Switchover valve
    29 Switchover valve

  - 29 Switchover valve
    30 Vacuum lines
    34 Check valve
    38 Specified leak points
    80 Switchover valve ("BI-LEVEL")
    81 Vacuum switch (at "BI-LEVEL" only)

  - 82 Check valve 83 Check valve



- 9 Energize switchover valve.
- 10 Connect tester to switchover valve connection E and evacuate.
- 11 If gauge shows pressure increase, switchover valve is leaking and should be replaced.