MAINTENANCE SERVICE - EVERY 10,000 MILES



All 1974 Models (With #3Z At 30,000 Mile Intervals)

Customer:	Work Order No.:
Address:	License No.:
City & State:	Mileage:
Zip Code or Province:	Time Promised:
Maintenance Work to be Performed: ☐ MB Maintenance Service (three sections) with engine oil change and oil filter service. ☐ Oil: Brand-Viscosity	Special Maintenance Work Performed at Extra Cost: Sliding Roof: Clean guide channels and lubricate lightly. Lighting System: Check headlights and aim. Battery: Clean housing and terminals; grease terminals lightly. Paint finish and chrome care. Clean Engine and Engine Compartment: lubricate all control linkages. Special Instructions from Customer:
Visual Inspection: Check For Leakage and General Cond	dition.
☐ Engine ☐ Rear Axle	☐ Front Axle ☐ Undercarriage
☐ Steering☐ Brakes☐ Transmission☐ Shock Absorbers	☐ Tires ☐ Body Condition ☐ Exhaust System
☐ Transmission ☐ Shock Absorbers	
Result:	
Part I: Service Maintena	ance with Oil Filter Change
O 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	O 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Inspection for Leaks and Condition	(manual transmission only). 766 Throttle valve, clean
O38 Heating & cooling system.	(California only)
	(continued)

Page 2

MBNA/MBC 2023 (Rev. 5-83)

Additional Maintenance Work to be Performed Every 30,000 Miles Maintenance Service #3Z

Maintenance 280C 280-280C 230 -082 **Tightening of Nuts and Bolts** Oil Change 871 Intake and exhaust manifold nuts and exhaust 170 Automatic transmission oil change. flange bolts. Filter Replacement or Cleaning Exhaust pipe flange only. 174 Automatic transmission: replace filter element. 876 Carburetor mounting flange screws 612 Power steering: Replace filter element. 851 Fuel feed pump; clean screen (carburetor engines only). Checking 840-847-849 Fuel filter: clean element or replace 501 Check clutch lining thickness (manual transmission only). 845 Fuel main filter: Clean filter element and filter housing 625 Check front wheel toe-in. 844 Fuel pre-filter: check 030 Check propeller shaft joint discs for wear or damage. □ □ □ 813 Check throttle control linkage. Lubrication ☐ ☐ ☐ 388 Front wheel grease caps: clean and refill with new grease. Date _ Service Manager (Signature)